

24-Port Gigabit Rack-mount Ethernet Switch

Model: S124GR



Product Introduction

The 24-port Gigabit Rack-mount Ethernet switch adopts high-quality and high-speed network ICs, and this product completely solves the problem of noise of small switches in the office environment through the fanless mute design. This switch has 24 Gigabit RJ45 ports, can provide seamless connection for 10/100/1000M Ethernet, supports three working modes, one-key smart simple switching working mode, easy to manage and maintain, the product can be widely used in Security network video surveillance, hotel, campus, small and medium-sized enterprise network engineering and other occasions.

Features

- © 24*10/100/1000M RJ45 Ports
- © Apply to IEEE802.3、IEEE802.3u、IEEE802.3ab standard
- © Ethernet port supports 10/100/1000M adaptive
- © Support auto MDI/MDIX
- © Panel indicators to monitor working status and help fault analysis
- © One-key smart switch, supports VLAN, Default, Extend three modes
- © Flow control, full duplex adopts IEEE802.3x standard, half duplex adopts Backpressure standard
- © Port 1-8 supports Qos data priority
- © Support Loop alarm

Specification

Model	S124GR
I/O Interface	
Power	AC input (100–240V)
Ethernet	24*RJ45 10/100/1000Mbps Ports
Performance	
Switching Capacity	48Gbps
Throughput	35.71Mpps
Packet Buffer	4M
MAC Address	8K
Jumbo Frame	4Kbytes
Transfer Mode	Store and forward
MTBF	100000 hour
Standard	
Network protocol	IEEE802.3 (10Base-T)
	IEEE802.3u (100Base-TX)
	IEEE802.3ab (1000Base-TX)
	IEEE802.3x (Flow control)
Industry Standard	EMI: FCC Part 15 CISPR (EN55032) class A
	EMS: EN61000-4-2 (ESD)、
	EN61000-4-5(Surge)
Network Medium	10Base-T : Cat3,4,5 or above UTP(≤100m)
	100Base-TX : Cat5 or above UTP(≤100m)
	1000Base-TX : Cat5 or above UTP(≤100m)
Protection	
Security Certificate	CE、FCC、RoHS
Environment	
Working Environment	Working Temperature: -10~50°C
	Storage Temperature: -40~70°C
	Working Humidity : 10%~90%, non-condensing
	Storage Temperature: 5%~90%, non-condensing
Indication	
LED Indicators	PWR (Power indicator) 、 Link (Network Link) 、 LOOP (Loop alarm) 、 1000M
DIP Switch	VLAN: Port Isolation, 1–22 ports are isolated each other, all communicate with uplink port 23/24;
	Default: Default mode, Support loop alarm; Extend: Monitor Mode, 1–22 ports support 100M speed reduction negotiation, support 250 meters in 10Mbps/s mode, port 23 and port 24 as uplink port;
Mechanical	

Structure Size	Product Size: 440*204*44mm
	Package Size: 500*275*85mm
	Product Net-Weight: 2.2kg
	Product Gross-Weight: 2.7kg
Packing Info	MEAS: 520*445*300mm
	Packing Qty: 5unit
	Packing weight: 14.5KG
Power Voltage	Input Voltage : AC 100-240V,50/60Hz
	output voltage: 12V2A
Package List	Switch 1 pcs, Power cord 1 pcs, User manual 1 pc, Warranty card 1 pc, Brackets 1 pair
Package Contents	
Switch	1 pcs
Power cord	1 pcs
Hanging Ears	1 pcs
Quick installation guide	1 pcs



HIMAX



HIMAX TECHNOLOGY LIMITED

www.himax-technology.com

Email: sales@himax-technology.com

F10, Fuhong Building, No.120 Yongfu Road, Qiaotou Community Fuhai Street, BaoanDistrict, Shenzhen China



Company Website