

# 24GE+4Combo Full Gigabit Managed PoE Switch

Model: PS22404CG



## Product Introduction

The PS22404CG series is a gigabit L2+ managed PoE fiber switch. It has 4\*100/1000 combo ports and 24\*10/100/1000Base-T RJ45 ports. Port 1–24 can support IEEE 802.3af/at standard PoE power supply. single port PoE power reaches 30W, and the maximum PoE output power is 400W(at=600W). As a PoE power supply device, it can automatically detect and recognize the power receiving equipment that meets the standard and supply power through the network cable. It can supply power to POE terminal equipment such as wireless AP, webcam, VoIP phone, building visual access control intercom through network cable, to meet the network environment that needs high-density PoE power supply, suitable for hotels, campuses, parks, supermarkets, scenic spots, Factory quarters and SMB small and medium-sized enterprises form a cost-effective network.

The PS22404CG has the L2+ full network management, support IPV4/IPV6 management, static route full line rate forwarding, security protection mechanism, complete ACL/QoS policy and rich VLAN functions, and is easy to manage and maintain. Supports multiple network redundancy protocols STP/RSTP/MSTP (<50ms) and (ITU-T G.8032) ERPS to improve link backup and network reliability. When one-way network fails, communication can be quickly restored to ensure important Uninterrupted communication for applications. According to the actual application requirements, you can configure multiple application services such as PoE power management, port traffic control, VLAN division, and SNMP through the Web network management mode.

## Features

- ◎ 24GE+4\*Combo Managed PoE Switch,1–24 ports support IEEE 802.3af/at PoE
- ◎ Supports PoE power up to 30W for each port
- ◎ Supports PoE IEEE 802.3af/at compliant PDs
- ◎ Internal power adapter supply 400W
- ◎ WEB/CLI managed modes, SNMP bring abundant management features
- ◎ Support QVLAN,QoS and IGMP snooping optimize voice and video application

# Specification

Model	PS22404CG
Interfaces	
Fixed Port	24*10/100/1000Base-T/TX PoE ports (Data/Power) 4*combo ports (Data) 1 * RS232 console port (115200, N,8,1)
Ethernet Port	10/100/1000Base-T(X), Auto-Detection, Full/half duplex MDI/MDI-X self-adaption
Twisted Pair Transmission	10BASE-T: Cat3,4,5 UTP (≤100 meter) 100BASE-TX: Cat5 or later UTP (≤100 meter) 1000BASE-T: Cat5e or later UTP (≤100 meter)
SFP Slot Port	Gigabit SFP optical fiber interface, default matching optical modules (optional order single-mode / multi-mode, single fiber / dual fiber optical module. LC)
Optical Cable	Multi-mode: 850nm 0 ~ 550M, single mode: 1310nm 0 ~ 40KM, 1550nm 0 ~ 120KM.
Network Management Type	L2+
Network Protocol	IEEE802.3 10BASE-T; IEEE802.3i 10Base-T; IEEE802.3u 100Base-TX; IEEE802.3ab 1000Base-T; IEEE802.3z 1000base-X; IEEE802.3x.
Forwarding Mode	Store and Forward
Switch Property	
Switching Capacity	56Gbps (Non-blocking)
Forwarding Rate	26.78Mpps
MAC	8K
Buffer Memory	6M
Jumbo Frame	9.6K
LED Indicator	Power indicator: PWR (Green); Network indicator: 1-24(Link/Act)/ (Orange),25-28(Link/Act)/ (Green); POE indicator: PoE (Green) SYS:(Green)
Reset Switch	Yes, One-button factory reset
PoE Port	Port 1 to 24, IEEE802.3af/at @ POE
PoE Management	Total power limit of PoE power supply PoE output power allocation, off& af &at PoE output priority configuration PoE working status Delay start of power supply Scheduling of PoE operation and time

Power Supply Pin	Default 1/2 (+), 3/6 (-)	
Max Power Per Port	30W; IEEE802.3af/at	
Total PWR / Input Voltage	400W (AC100-220V)	
Power Consumption	Standby<8W, Full Load<400W	Standby<8W, Full Load<400W
Power Supply	Built-in power supply, AC 100~220V 50~60Hz	Built-in power supply, AC 100~220V 50~60Hz
Operation TEMP / Humidity	-20~+55°C, 5%~90% RH Non condensing	
Storage TEMP / Humidity	-40~+75°C, 5%~95% RH Non condensing	
Dimension (L*W*H)	440*290*44.5mm	
Net /Gross Weight	<4.5kg / <5kg	<4.9kg / <5.5kg
Installation	Desktop, 19-inch 1U cabinet	
Protection	IEC61000-4-2(ESD): ±8kV contact discharge, ±15kV air discharge	
	IEC61000-4-5(Lightning protection/Surge): Power:CM±4kV/DM±2kV; Port: ±4kV	
Protection Level	IP30	
Certification	CCC, CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS	
Warranty	3 years, lifelong maintenance.	
Interface	IEEE802.3X (Full-duplex)	
	Port temperature protection setting	
	Port green Ethernet Energy-saving setting	
	Broadcast storm control based on port speed	
	The speed limit of the message flow in the access port. The minimum particle size is 64Kbps.	
Layer 3 Features	L2+ network management,	
	IPV4/IPV6 management	
	L3 soft routing forwarding,	
	Static route, Default route @ 128 pcs, APR @ 1024 pcs	
VLAN	4K VLAN based on port, IEEE802.1q	
	VLAN based on the protocol	
	VLAN based on MAC	
	Voice VLAN, QinQ configuration	
	Port configuration of Access, Trunk, Hybrid	
Port Aggregation	LACP, Static aggregation	
	Max 9 aggregation groups and 8 ports per group.	
Spanning Tree	STP (IEEE802.1d), RSTP (IEEE802.1w), MSTP (IEEE802.1s)	
Industrial Ring Network Protocol	G.8032 (ERPS), Recovery time less than 20ms	
	250 Ring at most, Max 254 devices per ring.	
Multicast	MLD Snooping v1/v2, Multicast VLAN	

	IGMP Snooping v1/v2, Max 250 multicast groups, Fast log out
Port Mirroring	Bidirectional data mirroring based on port
QoS	Flow-based Rate Limiting
	Flow-based Packet Filtering
	8*Output queues of each port
	802.1p/DSCP priority mapping
	Diff-Serv QoS, Priority Mark/Remark
ACL	Queue Scheduling Algorithm (SP, WRR, SP+WRR)
	Port-based Issuing ACL, ACL based on port and VLAN
Security	L2 to L4 packet filtering, matching first 80 bytes message. Provide ACL based on MAC, Destination MAC address, IP Source, Destination IP, IP Protocol Type, TCP/UDP Port, TCP/UDP Port Range, and VLAN, etc.
	IP-MAC-VLAN-Port binding
	ARP inspection, Anti-DoS attack
	AAA & RADIUS, MAC learning limit
	Mac black holes, IP source protection
	IEEE802.1X & MAC address authentication
	Broadcast storm control, Backup for host datum
	SSH 2.0, SSL, Port isolation, ARP message speed limit
DHCP	User hierarchical management and password protection
	DHCP Client, DHCP Snooping, DHCP Server, DHCP Relay
Management	One-key recovery
	Cable Diagnose, LLDP
	Web Management (HTTPS)
	NTP, System work log, Ping Test
	CPU instant utilization status view
	Console/AUX Modem/Telnet/SSH2.0 CLI
	Download & Management on FTP, TFTP, Xmodem, SFTP, SNMP V1/V2C/V3
	NMS – smart network management system platform (LLDP+SNMP)
System	Category 5 Ethernet network cable
	Web browser: Mozilla Firefox 2.5 or higher, Google browser chrome V42 or higher, Microsoft Internet Explorer10 or later;
	TCP/IP, network adapter, and network operating system (such as Microsoft Windows, Linux, or Mac OS X) installed on each computer in a network
Certification	
Certification	CE, FCC, RoHS,
Package Contents	
Switch	1 pcs

Hanging Ears	1 pcs
--------------	-------

Power cord	1 pcs
------------	-------

Quick installation guide	1 pcs
--------------------------	-------



# HIMAX



HIMAX TECHNOLOGY LIMITED

[www.himax-technology.com](http://www.himax-technology.com)

Email: [sales@himax-technology.com](mailto:sales@himax-technology.com)

F10, Fuhong Building, No.120 Yongfu Road, Qiaotou Community Fuhai Street, BaoanDistrict, Shenzhen China



Company Website